



Material Safety Data Sheet(MSDS)

Report No : TST20240912221-8EN

Date: Sept.12, 2024

Page 1 of 6

Section 1 - Product and Company Identification

Applicant : LashbrandsKft.
1145 Budapest,Columbus utca 16/16.

Product Name : Eyelash Extension Glue Black Flash

Model number : UV glue 、 Quick glue 、 Eyelash Extension Glue

Emergency Contact : +36706104930

Email address : info@lashbrands.eu

Photo :



Signed for and on behalf of

Andy Zheng



Andy Zheng
Technical Director

Unless otherwise agreed in writing, this document is issued by the company subject to its general conditions of service printed overleaf, available on request or accessible at <http://www.tst-test.com>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of TST, this test report shall not be copied except in full and published as advertisement.

Dongguan True Safety Testing Co., Ltd.

Room 201, No.20, East of Houjie Avenue, Houjie, Dongguan, Guangdong, China

Tel:86-769-85088050 4001086960 E-mail:tst@tst-test.com <http://www.tst-test.com>



Material Safety Data Sheet(MSDS)

Report No : TST20240912221-8EN

Date: Sept.12, 2024

Page 2 of 6

Section 2 – Hazards Identification information

Safety instructions:

S1/2: Keep sealed and stored away from children.

S26: In case of eye contact, flush immediately with plenty of water and seek medical attention.

S37/39: Wear appropriate protective clothing, gloves, and use protective glasses or face mask.

Route of invasion: ingestion and percutaneous absorption

Environmental hazard: the substance has no harm to the environment before curing, and the typical polymer has no direct harm to the environment after curing.

Explosion hazard: Explosion risk: flammable in case of open fire, no explosion risk.

Health hazard: Inhaled or ingested in large quantities, may cause breathing difficulties, respiratory tract burning sensation. Long-term exposure can cause skin irritation.

Section 3 - Composition/Information on Ingredients

Ingredient Name:

The difference between the single product and mixture: mixture

Constitutes:

Chemical Formula	CAS No.	Content/%
Ethyl cyanoacrylate	7085-85-0	80-90%
Polymethyl methacrylate	9011-14-7	5-10%
Photoinitiator	270586-78-2	0.5-1%

Section 4 - First Aid Measures

Skin contact: Remove the contaminated clothes, wash them with water, and then rinse your skin thoroughly with soapy water.

Eye contact: The eyelids were extracted and rinsed with large amounts of running water or normal saline for at least 5 minutes. seek medical advice.

Unless otherwise agreed in writing, this document is issued by the company subject to its general conditions of service printed overleaf, available on request or accessible at <http://www.tst-test.com>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of TST, this test report shall not be copied except in full and published as advertisement.

Dongguan True Safety Testing Co., Ltd.

Room 201, No.20, East of Houjie Avenue, Houjie, Dongguan, Guangdong, China

Tel:86-769-85088050 4001086960 E-mail:tst@tst-test.com <http://www.tst-test.com>



Material Safety Data Sheet(MSDS)

Report No : TST20240912221-8EN

Date: Sept.12, 2024

Page 3 of 6

Mass Inhalation: Gargle immediately, drink enough warm water, rushed to the hospital.

Mass Ingestion: Quickly leave the scene to the fresh air and keep breathing open. Give the inhaled carbon compounds (a mixture of oxygen and 6% carbon dioxide) during dyspnea; breathing stops and artificial respiration occurs immediately.

Section 5 - Fire Fighting Measures

Harmful combustion products: carbon monoxide (CO).

Extinguishing method: Firefighters must wear gas masks and full-body firefighting suits to fight the fire upwind. Move containers from the scene of the fire to an open area if possible. Spray water to keep the fire container cool until the fire is extinguished. If the container in the fire changes color or the safety pressure relief device makes a sound, it must be evacuated immediately. Fire extinguishers with water are ineffective, and firefighters are protected with mist water.

Extinguishing media: foam, carbon dioxide, dry powder, sand.

Section 6 - Accidental Release Measures

Quickly evacuate personnel from the contaminated area to a safe area, isolate them, and strictly restrict entry and exit. Cut off the ignition source. It is recommended that emergency response personnel wear self-contained positive pressure respirators and protective clothing. Cut off the source of leakage as much as possible. Prevent flow into restricted spaces such as sewers and drainage ditches. Small leakage: Absorb with sand, vermiculite, or other inert materials. You can also rinse with a large amount of water, dilute the washing water and put it into the wastewater system. Massive leakage: Build embankments or dig pits for containment. Transfer to a tank truck or dedicated collector with a pump for recycling or transportation to a waste disposal site for disposal.

Unless otherwise agreed in writing, this document is issued by the company subject to its general conditions of service printed overleaf, available on request or accessible at <http://www.tst-test.com>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of TST, this test report shall not be copied except in full and published as advertisement.

Dongguan True Safety Testing Co., Ltd.

Room 201, No.20, East of Houjie Avenue, Houjie, Dongguan, Guangdong, China

Tel:86-769-85088050 4001086960 E-mail:tst@tst-test.com <http://www.tst-test.com>



Material Safety Data Sheet(MSDS)

Report No : TST20240912221-8EN

Date: Sept.12, 2024

Page 4 of 6

Section 7 - Handling and Storage

Operation precautions: Provide good natural ventilation conditions. Keep away from fire and heat. No smoking in the workplace. Use explosion-proof ventilation systems and equipment. When handling, light loading and unloading should be done to prevent damage to packaging and containers. 3. Do not arbitrarily change the resin packaging. 4. Select the appropriate resin container when packing. (e.g., PE, PP plastic drums, stainless steel drums, resin-coated carbon steel drums, or glassware)

Storage precautions: Store in a cool, ventilated warehouse. Keep away from fire and heat. Equipped with the corresponding variety and quantity of fire equipment.

Section 8 - Exposure Controls & Personal Protection

Engineering Control: Strengthen ventilation during production. Safety showers and eye wash facilities are provided.

Respiratory protection: Self-priming filter respirators (full face masks) or direct respirators (half face masks) must be worn when exposure to its vapors may occur. Wear self-contained breathing apparatus during emergency rescue or evacuation.

Eye Protection: Respiratory protection has been covered.

Body Protection: Wear rubber acid and alkali resistant clothing.

Hand Protection: Wear rubber acid and alkali resistant gloves.

Other protection: Smoking, eating and drinking are prohibited in the workplace, and hands should be washed before meals. After work, take a shower. Pay attention to personal hygiene.

Section 9-Physical and Chemical Properties

Appearance and Properties: Transparent liquid.

Odor: Slight pungent smell.

Boiling point (°C): No information available.

Decomposition temperature (°C): No information available.

Density: No information available.

Solubility: Insoluble in water, soluble in toluene, etc.

Unless otherwise agreed in writing, this document is issued by the company subject to its general conditions of service printed overleaf, available on request or accessible at <http://www.tst-test.com>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of TST, this test report shall not be copied except in full and published as advertisement.

Dongguan True Safety Testing Co., Ltd.

Room 201, No.20, East of Houjie Avenue, Houjie, Dongguan, Guangdong, China
Tel:86-769-85088050 4001086960 E-mail:tst@tst-test.com <http://www.tst-test.com>



Material Safety Data Sheet(MSDS)

Report No : TST20240912221-8EN

Date: Sept.12, 2024

Page 5 of 6

Section 10 - Stability & Reactivity Data

Stability: Stable at room temperature.

Conditions to Avoid: Heat, moisture.

Polymerization harm: light easy polymerization; Combustion (decomposition) products: carbon monoxide (CO), carbon dioxide (CO₂).

Section 11 - Toxicological Information

Acute toxicity:No information available.

Irritant: Avoid skin contact with eyes..

Sensitivity: No information available.

Carcinogenicity: No information available.

Section 12 - Ecological Information

Ecotoxicological toxicity:If many leak after , It is harmful to fish, harmful to aquatic organic matter and harmful to water source.

Bioconcentration: None.

Environment Migration: Not specifically documented.

Section 13 - Disposal Considerations

Nature of waste: hazardous waste.

Disposal method: When destroying the item in large quantities, the consent of the local public security fire protection, safety supervision and other agencies should be obtained.

Precautions: It is strictly forbidden to pour into the river when discarding.

Section 14 - Transport Information

Road transportation is handled in accordance with JT/T 617-2018: it is not restricted by rules.

Transport Fashion: By air, by sea, by railway, by road.

Transportation precautions: The packaging should be complete during transportation and the loading should be secure. During transportation, ensure that the packaging does not collapse, fall, or be damaged. Mixed shipment and transportation with oxidants, alkalis, edible chemicals, etc. are strictly prohibited.

Unless otherwise agreed in writing, this document is issued by the company subject to its general conditions of service printed overleaf, available on request or accessible at <http://www.tst-test.com>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of TST, this test report shall not be copied except in full and published as advertisement.

Dongguan True Safety Testing Co., Ltd.

Room 201, No.20, East of Houjie Avenue, Houjie, Dongguan, Guangdong, China

Tel:86-769-85088050 4001086960 E-mail:tst@tst-test.com <http://www.tst-test.com>



Material Safety Data Sheet(MSDS)

Report No : TST20240912221-8EN

Date: Sept.12, 2024

Page 6 of 6

Section 15 - Regulatory Information

EU CLP - Regulation (EC) No 1272/2008 on the Classification, Labeling and Packaging of substances and mixtures

REACH Regulation (EC) No 1907/2006

Commission Regulation (EU) 2020/878

Section 16 - Other Information

Other Information: the above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the result of its use, this information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

TST confirmed the ninth item, the above content as reference information only. Please the user according to the demand to judge it usability. TST has no any responsibility.

*** End of Report ***

Unless otherwise agreed in writing, this document is issued by the company subject to its general conditions of service printed overleaf, available on request or accessible at <http://www.tst-test.com>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of TST, this test report shall not be copied except in full and published as advertisement.

Dongguan True Safety Testing Co., Ltd.

Room 201, No.20, East of Houjie Avenue, Houjie, Dongguan, Guangdong, China

Tel:86-769-85088050 4001086960 E-mail:tst@tst-test.com <http://www.tst-test.com>